

ATLAS HIVO SAE 0W-20 SP

HIGH PERFORMANCE, MULTIGRADE ENGINE OIL FOR GASOLINE

GENERAL CHARACTERISTICS

- Atlas Hivo SAE 0W-20 SP is an advanced synthetic engine oil that exceeds the latest API SP and ILSAC GF-6 sequences.
- Atlas Hivo SAE 0W-20 SP reduces internal friction within the engine so that the engine can deliver full power, while at the same time generating fuel savings.
- Atlas Hivo SAE 0W-20 SP is particularly well-suited for use with the latest "Downsized" engines equipped with Stop & Start technologies and hybrid engines which require very fluid synthetic engine oils. These oils are able to service a wide scope of engines thanks to the fully backward compatibility of API and ILSAC sequences.
- Atlas Hivo SAE 0W20 SP oils can help generate fuel savings without the need to change driving style. It is also suitable for the most demanding driving conditions (door-to-door, sporty driving styles, repeated start-ups, city and motorway driving).

PROPERTIES

- Extended Engine Durability
- Fuel Efficiency Boost
- Exceptional Low Temperature Performance
- Consistent Peak Performance
- Ultimate Engine Armor
- Green-Tech Compatibility

SPECIFICATIONS

- API SP
- ILSAC GF-6A

TYPICAL CHARACTERISTICS

Properties	Units	Method	Values
Density @15 °C	Kg/L	ASTM D4052	0.847
Kinematic Viscosity @40 °C	mm ² /s	ASTM D445	45
Kinematic Viscosity @100 °C	mm ² /s	ASTM D445	8.53
Viscosity Index	-	ASTM D2270	165
Pour Point	°C	ASTM D97	-40
Flash Point	°C	ASTM D92	245

The typical characteristics mentioned represent mean values.

SAFETY, HEALTH & ENVIRONMENT

Atlas Hivo motor engine oil is unlikely to have any significant health or safety hazard when properly used in recommended application and follow good standards of personal hygiene.

Avoid contact with skin. Use impermeable gloves while handling oil. After skin contact, wash immediately with soap and water.

Take used oil to authorized collection point. Do not discharge used oil in to drain, soil or water.