

ATLAS HIVO SAE 5W-30 SP

HIGH PERFORMANCE, MULTIGRADE ENGINE OIL FOR GASOLINE

GENERAL CHARACTERISTICS

- Atlas Hivo SAE 5W-30 SP is an advanced fully synthetic motor oil designed and formulated to ensure ultimate engine protection with reduces fuel consumption.
- It ensures a smooth and high-power output throughout your driving experience.
- Atlas Hivo SAE 5W-30 SP meets or exceeds the requirements of various manufacturers' standards which out per-forms conventional oils.
- Atlas Hivo SAE 5W30 SP engine oil can be used in all seasons and operating conditions (motorway, City traffic).

PROPERTIES

- Low Temperature Performance
- Consistent Peak Performance
- Wear Protection
- Fuel Efficiency
- Active Cleaning

SPECIFICATIONS

- API SP
- ILSAC GF-6A

TYPICAL CHARACTERISTICS

Properties	Units	Method	Values
Density @15 °C	Kg/L	ASTM D4052	0.849
Kinematic Viscosity @40 °C	mm ² /s	ASTM D445	57.23
Kinematic Viscosity @100 °C	mm ² /s	ASTM D445	10.11
Viscosity Index	-	ASTM D2270	166
Pour Point	°C	ASTM D97	-33
Flash Point	°C	ASTM D92	246

The typical characteristics mentioned represent mean values.

SAFETY, HEALTH & ENVIRONMENT

Atlas Hivo motor engine oil is unlikely to have any significant health or safety hazard when properly used in recommended application and follow good standards of personal hygiene.

Avoid contact with skin. Use impermeable gloves while handling oil. After skin contact, wash immediately with soap and water.

Take used oil to authorized collection point. Do not discharge used oil in to drain, soil or water.