

Atlas ATF Dexron III

PRODUCT DESCRIPTION

ATLAS Automotive Gear Oil is designed for heavy-duty applications. It provides exceptional wear protection, thermal stability, and corrosion resistance, ensuring durability in demanding conditions. This oil enhances gear performance, reduces friction, and prolongs gear life, making it ideal for off-road and high-load automotive gear systems.

BENEFITS

Improves performance and service life compared to previous Automatic Transmission Fluids (ATF), thus reducing maintenance.

- ✓ Excellent oxidation resistance which reduces deposit formation and prolongs transmission life.
- ✓ Ensures smooth, silent gear change and efficient power transfer under all service conditions thanks to its friction modifiers.
- ✓ Its high viscosity index ensures protection at high temperatures and excellent fluidity at low temperatures.
- ✓ Due to its high friction stability, it can help to save energy compared to other ATF fluids.
- ✓ Compatible with joints and seals.

TYPICAL CHARACTERISTICS

The physical and chemical properties shown in table are average value based on recent production, they are not limiting values. Minor variations which do not affect performance are to be expected in normal manufacture.

Characteristics	Units	Values
Appearance	Visual	Bright & Clear
Relative Density at 15 °C	g/ml	0.8380
Kinematics Viscosity at 100 °C	mm ² /sec	7.96
Kinematics Viscosity at 40 °C	mm ² /sec	33.77
Viscosity Index	-	201
Flash Point	°C	222
Pour Point	°C	-42

The typical characteristics mentioned represent mean values.

SAFETY, HEALTH & ENVIRONMENT

Atlas ATF Dexron III unlikely to have any significant health or safety hazard when properly used in recommended application and follow good standards of personal hygiene.

Avoid prolong contact with skin. Use impermeable gloves while handling oil. After skin contact, wash with soap and water.