

Atlas DIESEL Engine Oil 20W-50 CF/SF

MULTIGRADE ENGINE OIL FOR DIESEL ENGINE

GENERAL CHARACTERISTICS

Atlas Engine oil contains virgin base stock formulated with multiple additives and the latest technology; provides superior lubrication for modern as well as older diesel engines. Suitable for use in a wide range of heavy-duty applications and operating environments found in the trucking, construction, and agricultural industries

FEATURES AND BENEFITS

- Effective anti-wear properties protect the engine and extend engine life.
- Protects against Rust and Corrosion extending engine life.
- Deposit control maintains engine cleanliness, maintaining engine performance through oil drain interval
- Good oxidation stability gives longer oil life, maintaining oil quality.
- Reduced high-temperature oil thickening maintains oil condition

SPECIFICATIONS

API CF/SF

TYPICAL CHARACTERISTICS

Properties	Units	Method	Values
Density @15 °C	Kg/L	ASTM D4052	0.893
Kinematic Viscosity @40 °C	mm ² /s	ASTM D445	186
Kinematic Viscosity @100 °C	mm ² /s	ASTM D445	20
Viscosity Index	-	ASTM D2270	126
TBN	mg KOH / gm	ASTM D2896	8.5
Pour Point	°C	ASTM D97	-24
Flash Point	°C	ASTM D92	240

The typical characteristics mentioned represent mean values.

SAFETY, HEALTH & ENVIRONMENT

Atlas motor oil is unlikely to have any significant health or safety hazard when properly used in recommended application and follow good standards of personal hygiene.

Avoid contact with skin. Use impermeable gloves while handling oil. After skin contact, wash immediately with soap and water.

Take used oil to authorized collection point. Do not discharge used oil in to drain, soil or water.