

Atlas Deplus SAE-30 CD

MONOGRADE HEAVY-DUTY DIESEL ENGINE OIL

GENERAL CHARACTERISTICS

Applications: Can be used in those applications where the manufacturer recommends monograde diesel engine oil of API CD Performance and SAE 30 Viscosity such as in:

- High-speed, four-stroke, turbocharged or naturally aspirated Diesel engines
- Generator Sets
- Off-highway vehicles
- Agricultural tractors

PROPERTIES

- **Effective Engine Protection:** Monograde SAE-30 CD oil offers reliable protection against engine wear, ensuring a longer engine lifespan.
- **Improved Fuel Efficiency:** Enhanced lubrication reduces friction, leading to better fuel economy and cost savings.
- **Cleaner Engine Operation:** This oil minimizes deposits and sludge, resulting in a cleaner and more efficient engine.
- **Cost-Effective Maintenance:** With superior protection and efficiency, you'll experience reduce maintenance expenses and overall savings.

SPECIFICATIONS

API CD

TYPICAL CHARACTERISTICS

Properties	Units	Method	Values
Density @15 °C	Kg/L	ASTM D4052	0.886
Kinematic Viscosity @100 °C	mm ² /s	ASTM D445	12.4
Kinematic Viscosity @40 °C	mm ² /s	ASTM D445	100
Viscosity Index	-	ASTM D2270	104
Pour Point	°C	ASTM D97	-18
Flash Point	°C	ASTM D92	235

The typical characteristics mentioned represent mean values.

SAFETY, HEALTH & ENVIRONMENT

Atlas Deplus SAE 30 is unlikely to have any significant health or safety hazard when properly used in recommended application and follow good standards of personal hygiene.

Avoid contact with skin. Use impermeable gloves while handling oil. After skin contact, wash immediately with soap and water.

Take used oil to authorized collection point. Does not discharge used oil in to drain, soil or water.