

Atlas HIVO SAE 10W-40 SN PLUS

HIGH PERFORMANCE, MULTIGRADE ENGINE OIL FOR GASOLINE ENGINE

GENERAL CHARACTERISTICS

Atlas Hivo SAE 10W-40 Premium quality motor engine oil. Formulated with the use of synthetic technology for ultimate performance and protection under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

PROPERTIES

- Long drain interval formulated for excellent product stability. Long lasting performance and suitable for long drain intervals.
- Engine cleanliness keeps the engine extremely clean by minimizing deposits.
- Wear protection provides ultimate protection against wear under all operating conditions.
- Excellent cold start performance instant oil flow at low temperatures provides easy cold starts and optimal lubrication within seconds after ignition
- Deposit control special additives prevent the formation of sludge and harmful deposits inside the engine

SPECIFICATIONS

API SN PLUS

TYPICAL CHARACTERISTICS

| Properties | Units | Method | Values |
|-----------------------------|--------------------|------------|--------|
| Density @15 °C | Kg/L | ASTM D4052 | 0.858 |
| Kinematic Viscosity @40 °C | mm ² /s | ASTM D445 | 101 |
| Kinematic Viscosity @100 °C | mm ² /s | ASTM D445 | 14.2 |
| Viscosity Index | - | ASTM D2270 | 156 |
| Pour Point | °C | ASTM D97 | -33 |
| Flash Point | °C | ASTM D92 | 235 |

The typical characteristics mentioned represent mean values.

SAFETY, HEALTH & ENVIRONMENT

Atlas motor oil A5+ is unlikely to have any significant health or safety hazard when properly used in recommended application and follow good standards of personal hygiene.

Avoid contact with skin. Use impermeable gloves while handling oil. After skin contact, wash immediately with soap and water.

Take used oil to authorized collection point. Do not discharges used oil in to drain, soil or water.